

# **TECHNICAL LITHIUM IRON PHOSPHATE BATTERY DATA** 36V 40AH LIFEPO4 BATTERY

## **DIMENSIONS**

LENGTH	WIDTH	HEIGHT	WEIGHT	Remark
20.6 in.	9.33 in.	8.5 in.	35 lb.	With case



#### **PRODUCT SPECIFICATIONS**

NOMINAL VOLTAGE	38.4V	CELL CONFIGURATION	A123 3.2V20AH
NOMINAL CAPACITY	40AH	TOTAL CELLS	24 pieces
DISCHARGE CUT-OFF	30V	IMPEDANCE	≤20 mΩ
CHARGE CUT-OFF	43.8V	DISCHARGE TEMPERATURE RANGE	-4°F ~ 140°F -20*C ~ 60°C
CHARGE CURRENT	20A	CHARGE TEMPERATURE RANGE	32°F ~ 113°F 0*C ~ 45°C
CONTINUOUS DISCHARGE CURRENT	40A	CHARGE METHOD	CC/CV
PEAK DISCHARGE	80A	CYCLE LIFE	2000–5000

NOTE: IF YOU NEED HIGHER CHARGE/DISCHARGE/PEAK CURRENT, PLEASE LET US KNOW; WE CAN MAKE UP THE GRADE MODEL

#### **ENERGY CAPACITY HOURS**

@ 4AH	@ 10AH	@ 40AH	TOTAL ENERGY
10HR	4HR	1HR	1536 Wh

## **INTERNAL DESIGN**

BOLTED	WELDED
	X

#### **FEATURES & PERFORMANCE**

- 2000-5000 LIFE CYCLES
- INCREASED SAFETY PERFORMANCE
- WIDE OPERATING TEMPERATURE RANGE
- HIGH TEMPERATURE PERFORMANCE
- GREEN ENERGY WITHOUT CONTAMINANTS
- PRESSURE RESISTANT CELLS
- HIGH CAPACITY SYSTEM
- STEADY OUTPUT VOLTAGE
- <3% YEARLY DISCHARGE STORAGE
- TRIPLE SAFETY PROTECTION
- VIBRATION & SHOCK RESISTANT
- NO MEMORY EFFECT

#### **SAFETY PROTECTION**

- OVER CHARGING
- OVER DISCHARGING
- SHORT CIRCUIT
- PENETRATION
- THERMAL SHOCK
- NO FIRES
- NO EXPLOSIONS

#### **WARNINGS**

- NEVER CONNECT THE POSITIVE AND THE NEGATIVE OF THE BATTERY WITH METAL
- NEVER SHIP OR STORE THE BATTERY WITH METAL
- NEVER CUT OR PUNCTURE THE BATTERY
- DO NOT EXPOSE THE BATTERY TO WATER
- DO NOT EXPOSE THE BATTERY TO FIRE & HIGH TEMPERATURES

## **STORAGE & NON-USE**

- STORE IN A DRY PLACE WITH TEMPERATURE NOT EXCEEDING 85°F OR 30°C
- FOR LONG-TERM STORAGE KEEP BATTERY CHARGED AT 30%-50% OF CAPACITY
- DO NOT STORE BATTERY WITH METAL
- USE TERMINAL POST COVERS TO PREVENT ANY SHORT CIRCUIT CIRCUMSTANCES

#### **WARRANTY TERMS**

LBS OFFERS A 2-YEAR FACTORY-BACKED WARRANTY THAT COVERS MANUFACTURER DEFECTS; WITHIN THE WARRANTY TIME FRAME, THE LIFEPO4 BATTERY COMPANY WILL REPAIR OR REPLACE THE BATTERY WITH A NEW OR REMANUFACTURED BATTERY.

**NOT COVERED BY WARRANTY:** 

- DAMAGE CAUSED BY ACCIDENTS OR ACTS OF GOD
- LOOSE TERMINAL BOLTS AND CORROSION
- FAILURE TO INSTALL THE BATTERY PROPERLY OR MAINTAIN & CHARGE IT
- FIRE, INTENSE HEAT, & FREEZING
- WATER DAMAGE AND MOISTURE
- TAMPERING OF THE BATTERY CASE

# **ADDITIONAL PRODUCT INFORMATION**

LBS MAKES EVERY ATTEMPT TO VERIFY THAT ITS PRODUCTS ARE USED AND DESIGNED FOR YOUR APPLICATION. FOR ADDITIONAL QUESTIONS OR CONCERNS PLEASE FEEL FREE TO CONTACT US AT +1(941)210-4921 OR AT INFO@LITHIUMBATTERYSTORE.COM

MORE INFORMATION ABOUT OUR WARRANTY AND PRODUCT GUIDELINES CAN

BE FOUND AT https://www.lithiumbatterystore.com/